



## Safety Data Sheet

**24 Hour Emergency Phone Numbers**  
**Medical/Poison Control:**  
 In U.S.: Call 1-800-222-1222

**Outside U.S.: Call your local poison control center**

**Transportation/National Response Center:**

**1-800-535-5053**  
**1-352-323-3500**

NOTE: The National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

### 1. Identification

This Safety Data Sheet is available in American Spanish upon request.  
 Los Datos de Seguridad pueden obtenerse en Espanol si lo requiere.

<b>Product Name:</b>	Max Strength Heavy Duty Construction Adhesive	<b>Revision Date:</b>	4/11/2022
<b>Product UPC Number:</b>	070798748804	<b>Supercedes Date:</b>	New SDS
<b>Product Use/Class:</b>	Caulking Compound	<b>SDS No:</b>	1714265
<b>Manufacturer:</b>	DAP Global Inc. 2400 Boston Street Suite 200 Baltimore, MD 21224-4723 888-327-8477 (non - emergency matters)	<b>Imported by:</b>	DAP Canada 475 Finchdene Square Unit 5 Scarborough, Ontario M1X 1B7 888-327-8477 (non - emergency matters)
	SDS Coordinator: MSDS@dap.com		SDS Coordinator: MSDS@dap.com
	Emergency Telephone: 1-800-535-5053, 1-352-323-3500, 1-800-222-1222		Emergency Telephone: 1-800-535-5053, 1-352-323-3500

**Preparer:** Regulatory and Environmental Affairs

### 2. Hazards Identification

**GHS Classification**

Acute Tox. 4 Inhalation

**Symbol(s) of Product****Signal Word**

Warning

**Possible Hazards**

84% of the mixture consists of ingredients of unknown acute toxicity

**GHS HAZARD STATEMENTS**

Acute Toxicity, Inhalation, category 4 H332 Harmful if inhaled.

**GHS LABEL PRECAUTIONARY STATEMENTS**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P271 Use only outdoors or in a well-ventilated area.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.

### 3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Limestone	1317-65-3	45-70	No Information	No Information
Silane-Terminated Polyurethane Resin	13497-18-2	10-30	No Information	No Information
1,2-Benzenedicarboxylic acid, di-C9-C11-branched	68515-49-1	5-10	GHS07	H332
Alkylsulfonic Acid Ester of Phenol	70775-94-9	1-5	No Information	No Information

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

### 4. First-aid Measures

**FIRST AID - INHALATION:** Material is not likely to present an inhalation hazard at ambient conditions. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water for 15 minutes. Get medical aid if symptoms persist.

**FIRST AID - EYE CONTACT:** In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

**FIRST AID - INGESTION:** If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

### 5. Fire-fighting Measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** No Information

**SPECIAL FIREFIGHTING PROCEDURES:** Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

**EXTINGUISHING MEDIA:** Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Spray or Fog

### 6. Accidental Release Measures

**ENVIRONMENTAL MEASURES:** No Information

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

### 7. Handling and Storage

**HANDLING:** KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Avoid breathing vapor and contact with eyes, skin and clothing. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Wash thoroughly after handling.

**STORAGE:** Avoid excessive heat and freezing. Store away from caustics and oxidizers.

## 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Limestone	N.E.	N.E.	15 mg/m3 TWA total dust, 5 mg/m3 TWA respirable fraction	N.E.
Silane-Terminated Polyurethane Resin	N.E.	N.E.	N.E.	N.E.
1,2-Benzenedicarboxylic acid, di-C9-C11- branched	N.E.	N.E.	N.E.	N.E.
Alkylsulfonic Acid Ester of Phenol	N.E.	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation  
Sk = Skin Sensitizer N.E. = Not Established

### Personal Protection



**RESPIRATORY PROTECTION:** No personal respiratory protective equipment normally required.



**SKIN PROTECTION:** Wear nitrile or neoprene gloves.



**EYE PROTECTION:** Goggles or safety glasses with side shields.



**OTHER PROTECTIVE EQUIPMENT:** Not required under normal use.



**HYGIENIC PRACTICES:** Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

## 9. Physical and Chemical Properties

<b>Appearance:</b>	White to Off-White	<b>Physical State:</b>	Paste
<b>Odor:</b>	Slight	<b>Odor Threshold:</b>	Not Established
<b>Density, g/cm3:</b>	1.71 - 1.71	<b>pH:</b>	Not Applicable
<b>Freeze Point, °C:</b>	Not Established	<b>Viscosity (mPa.s):</b>	Not Established
<b>Solubility in Water:</b>	Not Established	<b>Partition Coeff., n-octanol/water:</b>	Not Established
<b>Decomposition Temperature, °C:</b>	Not Established	<b>Explosive Limits, %:</b>	N.E. - N.E.
<b>Boiling Range, °C:</b>	100 - 100	<b>Auto-Ignition Temperature, °C</b>	Not Established
<b>Minimum Flash Point, °C:</b>	100	<b>Vapor Pressure, mmHg:</b>	Not Established
<b>Evaporation Rate:</b>	Slower Than n-Butyl Acetate	<b>Flash Method:</b>	Seta Closed Cup
<b>Vapor Density:</b>	Heavier Than Air	<b>Flammability, NFPA:</b>	Non-Flammable
<b>Combustible Dust:</b>	Does not support combustion		

(See "Other information" Section for abbreviation legend)  
(If product is an aerosol, the flash point stated above is that of the propellant.)

## 10. Stability and Reactivity

**STABILITY:** Stable under recommended storage conditions.

**CONDITIONS TO AVOID:** Excessive heat and freezing.

**INCOMPATIBILITY:** Incompatible with strong bases and oxidizing agents.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Normal decomposition products, i.e., COx, NOx.

## 11. Toxicological Information

**EFFECT OF OVEREXPOSURE - INHALATION:** Under normal use conditions, this product is not expected to cause adverse health effects. During application and cure, this product releases methanol. Methanol may affect the brain or nervous system causing dizziness, headache or nausea. Inhalation of vapors in high concentration may cause mild irritation of respiratory system (nose, mouth, mucous membranes).

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Under normal use conditions, this product is not expected to cause adverse health effects. Prolonged or repeated contact with skin may cause mild irritation.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** Under normal use conditions, this product is not expected to cause adverse health effects. Direct eye contact may cause irritation.

**EFFECT OF OVEREXPOSURE - INGESTION:** Under normal use conditions, this product is not expected to cause adverse health effects. Single dose oral toxicity is very low. Amounts ingested incidental to industrial handling are not likely to cause injury; however, ingestion of large amounts may cause injury. Ingestion may result in obstruction when material hardens.

**CARCINOGENICITY:** No Information

**EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS:** Repeated or prolonged exposure may cause mild irritation of eyes and skin. Constituents of this product include crystalline silica which, if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

**PRIMARY ROUTE(S) OF ENTRY:** Skin Contact, Inhalation

### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
1317-65-3	Limestone	6450 mg/kg Rat	N.I.	N.I.
13497-18-2	Silane-Terminated Polyurethane Resin	N.I.	>2000 mg/kg Rat	N.I.
68515-49-1	1,2-Benzenedicarboxylic acid, di-C9-C11-branched	>60000 mg/kg Rat	16000 mg/kg Rabbit	>12.54 mg/L Rat
70775-94-9	Alkylsulfonic Acid Ester of Phenol	N.I.	N.I.	N.I.

N.I. = No Information

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Ecological injuries are not known or expected under normal use.

## 13. Disposal Information

**DISPOSAL INFORMATION:** This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261. Dispose as hazardous waste according to all local, state, federal and provincial regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

## 14. Transport Information

**SPECIAL TRANSPORT PRECAUTIONS:** No Information

**DOT UN/NA Number:** N.A.  
**DOT Proper Shipping Name:** Not Regulated  
**DOT Technical Name:** N.A.  
**DOT Hazard Class:** N.A.  
**Hazard SubClass:** N.A.  
**Packing Group:** N.A.

## 15. Regulatory Information

### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

### TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

## 16. Other Information

**Revision Date:** 4/11/2022 **Supersedes Date:** New MSDS  
**Reason for revision:** HazCom2012/GHS Conversion  
**Datasheet produced by:** Regulatory Department

### HMIS Ratings:

Health:	Flammability:	Reactivity:	Personal Protection:
1	0	0	X

VOC Less Water Less Exempt Solvent, g/L: 8.4

VOC Material, g/L: 8

VOC as Defined by California Consumer Product Regulation, Wt/Wt%: 0.06

VOC Actual, Wt/Wt%: 0.5

### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H332 Harmful if inhaled.

### Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS07



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.